

CLEAN COPY OF REPLACEMENT CLAIMSIN THE CLAIMS:

J1
74. (amended) An optical-fiber transmission system, comprising a cable closure body and fiber optic cables, said system further comprising:

(a) cable lead-in spigots, said cable lead-in spigots being attached to said cable closure body and being in communication with an interior space of the closure body;

(b) said fiber optic cables comprising waveguide-receiving pipes and optical waveguides, said waveguide-receiving pipes respectively having at least one optical waveguide therein, said waveguide-receiving pipes being respectively associated with said lead-in spigots; and

2ul
K,
(c) said waveguide-receiving pipes being connected to said lead-in spigots by respective sealing connections, said waveguide-receiving pipes terminating at said sealing connection and being disposed exteriorly of said closure body interior space, and respective said waveguides passing said sealing connections and entering said closure body interior space, wherein said sealing connections comprise respective sleeves having respective interior surfaces, said interior surfaces fittingly contacting said lead-in spigots and said waveguide-receiving pipes.

J2
79. (amended) The system of claim 74, said interior space of said closure body comprising a base section, said base section having a domed shape.

Please add the following new claims:

81. (new) An optical-fiber transmission system, comprising a cable closure body and a fiber optic cable, said system further comprising:

J3
K2
(a) cable lead-in spigots, said cable lead-in spigots being

53
cont
2
5
and

attached to said cable closure body and being in communication with an interior space of the closure body, said lead-in spigots having a terminal end section;

(b) said fiber optic cables comprising waveguide-receiving pipes and optical waveguides, said waveguide-receiving pipes respectively having at least one optical waveguide therein, said waveguide-receiving pipes being respectively associated with said lead-in spigots, said waveguide-receiving pipes havin a terminal end section; and

(c) said waveguide-receiving pipes being connected to said lead-in spigots by respective sealing connections, said waveguide-receiving pipes terminating at said sealing connection and being disposed exteriorly of said closure body interior space so that respective terminal end sections of the lead-in spigots and the waveguide-receiving pipes are in contact, and respective said waveguides passing said sealing connections and entering said closure body interior space.

82. (new) The system of claim 81, said sealing connection comprising a welded, soldered, crimped, shrink tube, or bonded connection.

83. (new) The system of claim 81, said interior space of said closure body comprising a base section, said base section having a domed shape.

84. (new) The system of claim 81, said lead-in spigots comprising respective pipes, said waveguide-receiving pipes being respectively sealingly connected to the lead-in spigot pipes, said sealing connections thereby formed inhibiting movement of the cable pipes with respect to the lead-in spigots.

85. (new) The system of claim 81, said interior space being

defined by a wall surface of the closure body, said wall surface comprising at least one ledge for supporting a waveguide tray.

53
part
ent
to

86. (new) An optical-fiber transmission system, comprising a cable closure body and fiber optic cables, said system further comprising:

(a) an interior space of said cable closure body, said interior space being defined by a wall surface of the closure body, said wall surface comprising at least one ledge for supporting a waveguide tray;

(b) cable lead-in spigots, said cable lead-in spigots being attached to said cable closure body and being in communication with said interior space of the closure body;

(c) said fiber optic cables comprising waveguide-receiving pipes and optical waveguides, said waveguide-receiving pipes respectively having at least one optical waveguide therein, said waveguide-receiving pipes being respectively associated with said lead-in spigots; and

(d) said waveguide-receiving pipes being connected to said lead-in spigots by respective sealing connections, said waveguide-receiving pipes terminating at said sealing connection and being disposed exteriorly of said closure body interior space, and respective said waveguides passing said sealing connections and entering said closure body interior space.

87. (new) The system of claim 86, said sealing connection comprising a welded, soldered, crimped, shrink tube, or bonded connection.

88. (new) The system of claim 86, said interior space of said closure body comprising a base section, said base section having a domed shape.

53
end

89. (new) The system of claim 86, said lead-in spigots comprising respective pipes, said waveguide-receiving pipes being respectively sealingly connected to the lead-in spigot pipes, said sealing connections thereby formed inhibiting movement of the cable pipes with respect to the lead-in spigots.

90. (new) The system of claim 86, said lead-in spigots and said waveguide-receiving pipes having respective terminal end sections, said respective end sections being in contact.
